




R32
NEW

The 1st Full-inverter
Dehumidifier

FULL-INVERTER DEHUMIDIFIER SPECS (R32)

Model	IDHR60	IDHR96	IDHR120
Advised pool surface (m ²) *	≤25	≤40	≤50
Operating air temperature (°C)	10~38		
Capacity (l/h) (Air 30°C , RH 80%) *	2.5	4.0	5.0
DER (l/h.kW) (Air 30°C , RH 80%) *	4.00~3.40	4.53~4.05	4.50~3.68
Heat recovered (kW)	2.4	3.3	4.4
Electric heating optional (kW)	2	2	2
Rated power (kW)	0.11~0.73	0.17~0.99	0.22~1.36
Rated current (A)	0.48~3.17	0.74~4.30	0.96~5.91
Power supply	230V/1 Ph/50Hz		
Sound pressure at 1 m dB(A)	35.3~45.6	35.6~46.1	35.9~46.4
Air flow (m ³ /h)	600	800	1000
Net dimension LxWxH (mm)	850x291x770	1120x291x770	1220x291x770
Net weight (Kg)	53	68	72
Qty per 20'FT / 40'HQ (sets)	84/258	60/195	58/189

* Above data is subject to modification without notice.



1st Full-inverter Dehumidifier



50% power consumption of traditional dehumidifier



10
times

quieter than traditional
dehumidifier, quieter than
a fridge

×10



- Metal & Aluminum
-alloy perfectly match



- Environment
friendly
refrigerant


R32